

**DEVELOP**

Dynamic balance

[www.develop.eu](http://www.develop.eu)



# ineo 4000i



- > Black & white  
A4 printer
- > Up to 40 ppm

## Option diagram

### 1 Media Input

Paper tray  
PF-P23

Paper tray  
PF-P24

Copier Desk  
SCD-5000x

### 2

### 2 Media output

Convenience stapler  
EH-C591



### legend

- Mandatory option
- Option
- This option can only be installed with the respective option above it

## Finishing functionalities



Duplex



Corner  
stapling  
(offline)

## Description

### Media Input

PF-P23 Paper tray	250 sheets; A5–A4; 60–120 g/m <sup>2</sup>
PF-P24 Paper tray	520 sheets; A5–A4; 60–120 g/m <sup>2</sup>
SCD-5000x Copier desk	Provides storage space for print media and other materials

### Media output

EH-C591 Convenience stapler	20-sheet off-line stapling
-----------------------------	----------------------------

## Technical specifications

### SYSTEM SPECIFICATIONS

Panel size/resolution	1 line LCD
System memory (standard/max)	256 MB (standard/max)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4 / IPv6); LPD; IPP; SNMP; HTTP; HTTP(S)
Paper input capacity (standard/max)	570 sheets / 1,610 sheets (standard/max)
Paper Tray 1	1x 520 sheets; A6–A4; 60–120 g/m <sup>2</sup>
opt. Paper Tray 1 - Total	1x 250 sheets; A5–A4; 60–120 g/m <sup>2</sup> (up to 2x)
opt. Paper Tray 2 - Total	1x 520 sheets; A5–A4; 60–120 g/m <sup>2</sup> (up to 2x)
Manual bypass	50 sheets; A6–A4; custom sizes; 60–200 g/m <sup>2</sup>
Automatic duplexing	A4; 60–105 g/m <sup>2</sup>
Output Capacity (standard)	150
Print volume (monthly)	Rec. 5,000 pages; Max. 100,000 pages
Toner lifetime	Black up to 12,000 pages
Imaging unit lifetime	50,000
Power consumption	220–240 V / 50/60 Hz; Less than 640 W
System dimension (W x D x H)	373 x 388 x 287 mm (without options)
System weight	Approx. 12.4 kg (without options)

### PRINTER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Polymerized Toner
Print resolution	1,200 x 1,200 dpi
Print Speed A4 (mono/colour)	Up to 40 ppm
1st print out time A4 (mono/colour)	7.2 sec.
Warm-up time	Approx. 25 sec.
Page description language	PCL 6 (XL3.0); PostScript 3; XPS
Operating Systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	85 PCL Latin; 66 PostScript 3 Emulation Latin
Mobile Printing	Mopria (Android); Google Cloud Print; WiFi Direct

### SYSTEM FEATURES

Security Functions (standard)	SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; Secure print; Kerberos
Accounting Functions (standard)	Active Directory support (user name + password + e-mail + smb folder)
Software	Net Care Device Manager; Web Connection; Driver Packaging Utility



## DEVELOP

Konica Minolta Business Solutions Europe GmbH  
 Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 [www.develop.eu](http://www.develop.eu)

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.